

CE DECLARATION OF PERFORMANCE

According to the regulation (EU) Nr. 305 of the European Parliaments and of the Council of 09. March 2011

No.: DoP-0707/06-10

1. Type:

OSB/2, thickness 6 - 10 mm

2 Recipe no.:

Rec. 707

3. Intended use:

Structural components for use under dry conditions,
type OSB/2 acc. to EN 300:2006

4. Trade name :

EGGER OSB 2

Manufacturer:

EGGER Romania S.R.L. Rădăuți
Str. Austriei 2,
725400 Rădăuți, jud. Suceava
Romania

5. not applicable

6. System of assessment and verification of constancy of performance acc. to Annex V of regulation (EU) No 305/2011:

System 2+

7. Construction product covered by :

EN 13986:2004

Notified body of the EU:

0765

Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 e
38108 Brunswick
Germany,

performed the initial inspection of the manufacturing plant and of the factory production control and the continuous surveillance,
assessment and evaluation of factory production control acc. to EN 13986:2004 System 2+
and issued the certificate of conformity of the factory production control:

195

8. not applicable


9. Declared Performance:

Essential characteristics	Performance			Harmonised technical specification
Thickness range	6 -10 mm			
Panel direction	0° (major axis)	90°(minor axis)		
Strength (N/mm²)				EN 13986:2004
- Bending	18,0	9,0		
- Compression	15,9	12,9		
- Tension	9,9	7,2		
- Planar Shear	6,8	6,8		
- Panel Shear	1,0	1,0		
Stiffness (N/mm²)				
- Tension	4930	1980		
- Compression	3800	3000		
- Bending	3800	3000		
- Planar Shear	1080	1080		
- Panel Shear	50	50		
Density	≥580 kg/m³ (determined)			
Punching shear (N/mm²)	NPD			
Reaction to fire	Class E			
Impact resistance	d≥9mm: Pass			
Water vapour permeability (dry/wet)	150			
Air permeability	NPD			
Release of formaldehyde	E 1			
Release of PCP	< 3ppm			
Airborne sound insulation (surface mass)	NPD			
Sound absorption	0,10 / 0,25			
Thermal Conductivity	0,13 W/(m*K)			
Racking resistance	EN 1995-1-1			
Embedment strength	EN 1995-1-1			
Durability				
- Internal Bond	≥0,34 N/mm²			
- Swelling in thickness	≤20%			
- Mechanical		kmod =	kdef =	
	SC 1	EN 1995-1-1, Tab. 3.1	EN 1995-1-1, Tab. 3.2	
- Biological	Use class 1			
Performance Floor EN 12871, OSB 0° major axis	Load category	thickness	c-c-span	
	A	NPD		
Performance Roof EN 12871, OSB 0° major axis	Load category	thickness	c-c-span	
	H	NPD		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Banciu Ioan Lucian
Managing Director Production



Badescu Decebal Florin
Managing Director Sales



Rădăuți, d. 22.07.2013